



Geïmpregneerd naaldhout



bruto afmeting (MM)	netto afmeting (MM)	werkende breedte (MM)	handels- lengtes (CM)	lange lengtes (CM)
------------------------	------------------------	--------------------------	--------------------------	-----------------------

Geïmpregneerde palen

VUREN GESCHAAFD

150	150	140	140	N.V.T.	250 - 300 - 360 - 420	N.V.T.
130	130	120	120	N.V.T.	210 - 240 - 270 - 300 - 360 - 420	N.V.T.
100	100	90	90	N.V.T.	210 - 240 - 270 - 300 - 360 - 420	N.V.T.
80	80	70	70	N.V.T.	210 - 240 - 270 - 300 - 360 - 420	N.V.T.

Geïmpregneerd constructiehout

VUREN GESCHAAFD

75	175	70	170	N.V.T.	300 - 360 - 390 - 420 - 480 - 510 - 540	N.V.T.
63	175	60	170	N.V.T.	300 - 360 - 390 - 420 - 480 - 510 - 540	N.V.T.
63	150	60	145	N.V.T.	300 - 330 - 360 - 420	N.V.T.
47	150	44	145	N.V.T.	300 - 360 - 390 - 420 - 480 - 510 - 540	N.V.T.
47	125	44	120	N.V.T.	300 - 360 - 390 - 420 - 480 - 510 - 540	N.V.T.
47	100	44	95	N.V.T.	200 - 300 - 360 - 420 - 540	N.V.T.
47	75	44	70	N.V.T.	240 - 270 - 300 - 360 - 420	N.V.T.
47	50	44	45	N.V.T.	270 - 300 - 510	N.V.T.
32	150	28	145	N.V.T.	300 - 360 - 420	N.V.T.
32	100	28	95	N.V.T.	300 - 360 - 420	N.V.T.
32	75	28	70	N.V.T.	300 - 360 - 420	N.V.T.
32	50	28	45	N.V.T.	300 - 360 - 420	N.V.T.
22	75	18	70	N.V.T.	180 - 420	N.V.T.

VUREN SLS

38	89	38	89	N.V.T.	300 - 360 - 420 - 540	N.V.T.
----	----	----	----	--------	-----------------------	--------

Dak & gevel

BLOKHUTPROFIEL

32	200	28	194	179	300 - 330 - 360 - 390 - 420 - 480 510 - 540	N.V.T.
----	-----	----	-----	-----	--	--------



Geïmpregneerd naaldhout

bruto afmeting (MM)		netto afmeting (MM)		werkende breedte (MM)	handels- lengtes (CM)	lange lengtes (CM)
32	150	28	144	134	180 - 210 - 240 - 270 - 300 - 330 - 360 390 - 420 - 480 - 510 - 540	N.V.T.
25	125	22	120	109	180 - 200 - 240 - 270 - 300 - 330 - 360 390 - 420	
ZWEEDS RABAT						
25	200	13/27	194	179	330 - 360 - 420 - 480 - 510 - 540	N.V.T.
HH RABAT						
22	175	18	170	155	330 - 360 - 420 - 480 - 510 - 540	N.V.T.
OH RABAT						
22	150	18	145	132	330 - 360 - 420 - 480 - 510 - 540	N.V.T.
GG						
22	150	18	145	132	330 - 360 - 420 - 480 - 510 - 540	N.V.T.
TRIPLE PROFIEL						
32	150	28	144	132	180 - 200 - 300 - 390 - 450	N.V.T.
DUO PROFIEL						
32	150	28	144	132	180 - 270 - 330 - 390 - 450	N.V.T.
HOEKPROFIEL						
63	63	59	59	N.V.T.	240 - 300	N.V.T.
50	50	45	45	N.V.T.	240 - 300	N.V.T.

Terras

TERRASDEEL - 1 Z GLANS 1 Z GROEF

32	150	28	145	145	300 - 360 - 420	N.V.T.
----	-----	----	-----	-----	-----------------	--------



Geïmpregneerd naaldhout

bruto afmeting (mm)		netto afmeting (mm)		werkende breedte (mm)	handels- lengtes (cm)	lange lengtes (cm)
Schutting						
SCHUTTINGPLANK						
22	150	18	145	145	180 – 240 – 300 – 360 – 420	N.V.T.
19	145	16	140	140	180 – 195 – 400	N.V.T.
AFDEKLAT SCHUIN						
38	88	34	80	N.V.T.	180 – 220	N.V.T.
AFDEKLAT PLAT						
22	88	20	80	N.V.T.	180 – 220	N.V.T.
BEUGELLAT						
19	50	15	45	N.V.T.	180	N.V.T.